



# Mesh grating 33/33

## Steel 240 YP

Manufactured in standard sizes or to special measurements. The distance between the bearing bars is 33 mm and 33 mm between filler bars. Grating 33/33 complies with the 35 mm ball requirement according to EN ISO 14122-2. A fastening bracket can be purchased for mounting to the structure.



### Specifications

PTV guidelines	25-35 Moderate Slip Potential
Dry PTV average	60
Wet PTV average	25
Slip resistance	R9 = 10° > slope > 6° acc. to DIN 51130
Displacement space	V10 acc. to DIN 51130
Free area	85 %
Distance between bearing bars (Ma)	33 mm
Distance between filler bars (Mc)	33 mm
Ball proof	35 mm in accordance with EN ISO 14122-2
	550 °C

## Featured cases

Little Belt Bridge - Public walkways and screening

## Accessories

Fixing clip, upper part Ma33

Fixing clip, lower part

## Related products

Fixing clip, upper part Ma33

Fixing clip, lower part

Plank Grating CUBE 30 Oyster

## Standard dimensions

Length (mm)	Width (mm)	Height (mm)	Mat. thickness (mm)	Edge bar (mm)	Finish	Availability	Item number
400	1000	25	2	25x3	Hot-dip galvanised	Stock item	F202210101
500	500	25	2	25x3	Hot-dip galvanised	Stock item	F202220101
500	1000	25	2	25x3	Hot-dip galvanised	Stock item	F202230101
500	1500	25	2	25x3	Hot-dip galvanised	Stock item	F202240101
600	500	25	2	25x3	Hot-dip galvanised	Stock item	F202250101
600	1000	25	2	25x3	Hot-dip galvanised	Stock item	F202260101
600	1500	25	2	25x3	Hot-dip galvanised	Stock item	F202270101
700	500	25	2	25x3	Hot-dip galvanised	Stock item	F202280101
700	1000	25	2	25x3	Hot-dip galvanised	Stock item	F202290101
700	1500	25	2	25x3	Hot-dip galvanised	Stock item	F202300101
750	1500	25	2	25x3	Hot-dip galvanised	Stock item	F202330101
800	500	25	2	25x3	Hot-dip galvanised	Stock item	F202340101
800	800	25	2	25x3	Hot-dip galvanised	Stock item	F202350101
800	1000	25	2	25x3	Hot-dip galvanised	Stock item	F202360101
800	1500	25	2	25x3	Hot-dip galvanised	Stock item	F202370101
900	500	25	2	25x3	Hot-dip galvanised	Stock item	F202380101
900	1000	25	2	25x3	Hot-dip galvanised	Stock item	F202390101
900	1500	25	2	25x3	Hot-dip galvanised	Stock item	F202400101
1000	500	25	2	25x3	Hot-dip galvanised	Stock item	F202410101
1000	600	25	2	25x3	Hot-dip galvanised	Stock item	F202420101
1000	800	25	2	25x3	Hot-dip galvanised	Stock item	F202430101
1000	1200	25	2	25x3	Hot-dip galvanised	Stock item	F202450101
500	1000	30	2	30x3	Hot-dip galvanised	Stock item	F202470101
600	1000	30	2	30x3	Hot-dip galvanised	Stock item	F202480101
800	1000	30	2	30x3	Hot-dip galvanised	Stock item	F202490101
1000	1000	30	2	30x3	Hot-dip galvanised	Stock item	F202500101
1000	1500	30	2	30x3	Hot-dip galvanised	Stock item	F202510101
1200	1000	30	2	30x3	Hot-dip galvanised	Stock item	F202520101
750	1000	25	2	25x3	Hot-dip galvanised	Stock item	F202320101
1000	1000	25	2	25x3	Hot-dip galvanised	Stock item	F202440101
1000	1500	25	2	25x3	Hot-dip galvanised	Stock item	F202460101
300	1000	30	2	30x3	Hot-dip galvanised	Stock item	F202530101

