



Mesh grating 33/11

Steel 240 YP

Manufactured in standard sizes or to special measurements. The distance between the bearing bars is 33 mm and 11 mm between filler bars. Grating 33/11 complies with the 15 mm ball requirement according to EN ISO 14122-2. A fastening bracket can be purchased for mounting to the structure.



Specifications

PTV guidelines	25-35 Moderate Slip Potential
Dry PTV average	66
Wet PTV average	35
Slip resistance	R9 = 10° > slope > 6° acc. to DIN 51130
Displacement space	V10 acc. to DIN 51130
Free area	74 %
Distance between bearing bars (Ma)	33 mm
Distance between filler bars (Mc)	11 mm
Ball proof	35 mm in accordance with EN ISO 14122-2 20 mm in accordance with EN ISO 14122-2 15 mm in accordance with EN ISO 14122-2
Fire resistance Critical temperature	550 °C

Featured cases

Little Belt Bridge - Public walkways and screening

Accessories

Fixing clip, lower part

Related products

Fixing clip, lower part

Standard dimensions

Length (mm)	Width (mm)	Height (mm)	Mat. thickness (mm)	Edge bar (mm)	Finish	Availability	Item number
300	1000	20	2	20x3	Hot-dip galvanised	Stock item	F202050101
400	800	20	2	20x3	Hot-dip galvanised	Stock item	F202060101
400	1000	20	2	20x3	Hot-dip galvanised	On request	F202080101
500	800	20	2	20x3	Hot-dip galvanised	On request	F202090101
500	1200	20	2	20x3	Hot-dip galvanised	On request	F202120101
500	1500	20	2	20x3	Hot-dip galvanised	On request	F202130101
600	800	20	2	20x3	Hot-dip galvanised	Stock item	F202140101
600	1000	20	2	20x3	Hot-dip galvanised	Stock item	F202150101
600	1200	20	2	20x3	Hot-dip galvanised	Stock item	F202160101
600	1500	20	2	20x3	Hot-dip galvanised	Stock item	F202170101
500	1000	20	2	20x3	Hot-dip galvanised	Stock item	F202110101
750	1000	25	2	25x3	Hot-dip galvanised	Stock item	F202180101
1000	1000	25	2	25x3	Hot-dip galvanised	Stock item	F202190101