


Plank Extr. 03

Aluminium 6060-T61

Optimo 03 Comprising of 14mm dia punched raised holes and 8.5mm dia depressed drainage holes. This punched profile provides excellent slip resistance, unsurpassed high strength to weight ratio and increased drainage owing to the larger holes giving a transparency of 28-32%.

- Manufactured in various combinations in relation to: - width, height, length and profile.
- Drainage
- High slip resistance
- Light weight.
- Bespoke sizes available
- Calculations & product data sheet / certificates available upon request.



Specifications

PTV guidelines	36+ Low Slip Potential
Dry PTV average	73
Wet PTV average	51
Slip resistance	R13 = slope >35° acc. to DIN 51130
Displacement space	V10 acc. to DIN 51130
Free area	28-32 %
Upward grip holes	dia. 14
Downward drainage holes	dia. 8,5 mm
C-C grid	36 x 36 mm
Ball proof	15 mm in accordance with EN ISO 14122-2 20 mm in accordance with EN ISO 14122-2 35 mm in accordance with EN ISO 14122-2


Suitable application areas

Access Walkways & Maintenance Platforms

Straight staircases

Standard dimensions

Length (mm)	Width (mm)	Height (mm)	Mat. thickness (mm)	Finish	Availability	Item number
6000	100	43	3	Mill finish	Stock item	C000016200p
6000	150	43	3	Mill finish	Stock item	C000026200p
6000	200	43	3	Mill finish	Stock item	C000036200p



Product name
OPTIMO Plank Extr O3