



Tread plank ACHIL VISUAL 02

Aluminium 3005-16 H66



image coming soon

Specifications

PTV guidelines	36+ Low Slip Potential
Dry PTV average	66
Wet PTV average	50
Slip resistance	R13 = slope >35° acc. to DIN 51130
Displacement space	V10 acc. to DIN 51130
Flange design	Achil [b]
Free area	20-25 %
Upward grip holes	dia. 9
Downward drainage holes	dia. 5 mm
C-C grid	25 x 25 mm
Load capacity	1,5 kN / 100 x 100 mm acc. to EN ISO 14122

Standard dimensions

Length (mm)	Width (mm)	Height (mm)	Mat. thickness (mm)	Finish	Availability	Item number
600	150	46	2.5	Mill finish	On request	C211006100
600	150	46	2.5	Washed	On request	C211006160
600	200	46	2.5	Mill finish	On request	C211016100
600	200	46	2.5	Washed	On request	C211016160
525	225	46	2.5	Mill finish	On request	C211026100
525	225	46	2.5	Washed	On request	C211026160
600	225	46	2.5	Mill finish	On request	C211036100
600	225	46	2.5	Washed	On request	C211036160
800	225	58	2.5	Mill finish	On request	C211046100
800	225	58	2.5	Washed	On request	C211046160