



Tread High visibility 05

Steel 240 YP

The new Achil 05HiVis treads offer all the benefits of the standard Achil tread. But with the added HiVis nosing which can be supplied in any standard RAL colour to suit either maintenance or public with DDA requirements. Ex stock in 2 sizes or our fully customised 05M Tread we can supply all stair sizes.



Specifications

PTV guidelines	36+ Low Slip Potential acc. to BS 7976
Dry PTV average	96 multi-directional acc. to BS 7976
Wet PTV average	79 multi-directional acc. to BS 7976
Slip resistance	R13 = slope >35° acc. to DIN 51130
Heel proof	
Flange design	Achil [b]
Free area	8-9 %
Upward grip holes	dia. 5 mm
Downward drainage holes	dia. 5 mm
C-C grid	25 x 25 mm
	3 kN / 100x100mm
Fire resistance Critical temperature	550 °C



PcP Gratings Ltd.
Enterprise Drive, Four Ashes, Wolverhampton, WV10 7DF

+44 1902 791 792
sales@pcp-corp-co.uk

Standard dimensions

Length (mm)	Width (mm)	Height (mm)	Thickness (mm)	Finish	Item No.
1000	300	57	2	Hot-dip galvanised EN 1461	F101140101
1200	300	57	2	Hot-dip galvanised EN 1461	F101160101