



Tread Futura, Press-lock 22/33

Steel 240 YP

Our mesh grating stair tread with high air flow is produced in many standard dimensions as well as custom dimensions.



Specifications

PTV guidelines	25-35 Moderate Slip Potential
Dry PTV average	60
Wet PTV average	25
Slip resistance	R9 = 10° > slope > 6° acc. to DIN 51130
Displacement space	V10 acc. to DIN 51130
Free area	85 %
Distance between bearing bars (Ma)	22 mm
Distance between filler bars (Mc)	33 mm
Fire resistance Critical temperature	550 °C

Suitable application areas

Straight staircases

Standard dimensions

Length (mm)	Width (mm)	Height (mm)	Finish	Weight (kg)	Availability	Item number
600	150	50	Hot-dip galvanised	3.60	On request	F250010101
700	150	50	Hot-dip galvanised	4.20	On request	F250020101
600	200	50	Hot-dip galvanised	4.40	Stock item	F250030101
700	200	50	Hot-dip galvanised	5.10	Stock item	F250040101
800	200	50	Hot-dip galvanised	5.80	Stock item	F250050101
700	250	50	Hot-dip galvanised	5.90	Stock item	F250070101
800	250	50	Hot-dip galvanised	6.70	Stock item	F250080101
1000	250	50	Hot-dip galvanised	8.30	Stock item	F250090101
800	300	50	Hot-dip galvanised	7.80	Stock item	F250100101
900	300	50	Hot-dip galvanised	8.50	Stock item	F250110101
1000	300	50	Hot-dip galvanised	9.80	Stock item	F250120101
1200	300	50	Hot-dip galvanised	13.00	Stock item	F250130101
900	250	50	Hot-dip galvanised	7.60	Stock item	F250140101
500	150	50	Hot-dip galvanised	3.10	On request	F250000101

End piece dimensions

Width (Pw) (mm)	Total height (Ht) (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)	K (mm)
150		35	15	13	13	17	78
200		45	15	13	13	17	102
250		50	15	13	13	17	142
300		50	15	13	13	17	190

